



1213

**DECLARATION OF PERFORMANCE**

according to Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011  
No.:DoP-310224-DD-40H-01-EN



1. Unique identification code of the product type:

**310224**

2. Type, batch or serial number or any other element allowing identification of the product as required under Article 11(4):

**DiaDrain-40H**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Flow-delay retention board for semi-intensive and intensive greenroofs and hard-surface pedestrian areas, with a height of 40 mm, made of recycled high-impact polystyrene (HIPS). As per standard:**

**EN 13252:2000/A1:2005**

**function: D**

4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**APP Kft.  
H-9028 Győr  
Fehérvári út 75.**

Tel.: +36 96 / 512 910  
Fax: +36 96 / 512 914  
[info@diadem.com](mailto:info@diadem.com)  
[www.diadem.com](http://www.diadem.com)

**APP Dachgarten GmbH  
Jurastrasse 21  
D-85049 Ingolstadt**

Tel.: +49 841 / 370 9496  
Fax: +49 841 / 370 9498  
[info@grundach.com](mailto:info@grundach.com)  
[www.grundach.com](http://www.grundach.com)

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):  
—

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**2+**

7. In case of the declaration of performance concerning product covered by harmonised standard:

**Notified factory production control certification body SKZ TeConA GmbH (1213) issued the certificate of conformity of the factory production control under system 2+ on the basis of: initial inspection of the manufacturing plant and of factory production control, and continuous surveillance, assessment and evaluation of factory production control.**

**Issued certificate: 1213-CPR-5419**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**not applicable**

9. Declared performance

Essential characteristics	Unit	Performance	Tolerance	Harmonised technical specification
Water flow capacity (MD, 20kPa, i=1)	m <sup>2</sup> /s	7.3 E-3	3.65 E-4	EN 12958:2010
Tensile strength MD	kN/m	4.25	-0.35	EN ISO 10319:2008
Tensile strength CMD	kN/m	3.91	-0.33	
Elongation MD	%	19.0	±1.31	
Elongation CMD	%	18.7	±2.41	
Durability	Has to be covered in 1 day after installation. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C			EN 13252:2000/A1:2005

**10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:

Laszlo Tarlos, Director of Product Development

Date: 01.06.2015. Győr, Hungary

Signature